

Astro → Air 20DA & 45DA

The AstroAir 20DA & 45DA can be clipped onto the AstroAir 25 and AstroAir 50 respectively to convert them into a double filtration unit. The benefits of using double filtration means that you can change the HEPA filter on the 45DA or 20DA at the completion of each job, without affecting the integrity of the DOP certification, therefore leaving the asbestos where it belongs in the work area. The 20DA & 45DA can also be used as roving heads to enable more flexibility with the use of separately available spigot plates.

Manufactured from 6mm and 5mm ABS thermoplastic sheet bonded to form triple welds.

LATCH



45DA



20DA



AstroAir Technical Specifications

Specifications		45DA	20DA
Volume M ³ /Hr		4500	2000
Power supply		n/a	n/a
Watts		n/a	n/a
Fuse		n/a	n/a
dB		n/a	n/a
Dimensions	Height	825mm	585mm
	Width	680mm	460mm
	Length	425mm	425mm
Weight		42kg	30kg
HEPA Filter	Height	610mm	385mm
	Width	610mm	385mm
	Length	292mm	292mm
Spigot Diameter		600mm	250mm
Castors x 4 (2 x braked)		100mm	100mm



For more information please visit us at www.mecanaka.co.uk or email us at info@mecanaka.co.uk

mECaNAKa Limited

Contamination Control Equipment

Unit D5, Heritage Business Park, Heritage Way, Gosport, Hampshire. PO12 4BG. United Kingdom

Tel: 02392 584414

Email: info@mecanaka.co.uk